



GENERAL

Name	Anni Selmer
Type	Mitsui 56
Built	January 2009
Flag	Cyprus
Class	Class NK
DWAT	55,639 mt on 12.573m (summer)
TPC	55.80 mts/cm (summer)
Tonnage	31,222 (GT) / 18,534 (NT)
LOA	189.99 m
Beam	32.26 m
Depth	17.90 m

SPEED & CONSUMPTION

Speed	Consumption		plus abt. 0.2 mt MDO/Day plus abt. 0.2 mt MDO plus abt. 0.2 mt MDO plus abt. 0.2 mt MDO
	laden	ballast	
abt. 14.5 kn		abt. 33.6 mt HFO	
abt. 14.0 kn	abt. 36.5 mt HFO		
abt. 12.0 kn	abt. 26.3 mt HFO	abt. 20.5 mt HFO	
abt. 11.0 kn	abt. 22.4 mt HFO	abt. 15.3 mt HFO	
	idle		plus abt. 0.2 mt MDO
		working	
Port	abt. 2.7 mt HFO	abt. 4.2 mt HFO	

Figures given basis clean and smooth bottom, deep water, even keel, no negative influence by currents, including 15% sea margin up to and incl. Beaufort Scale Force 4 and Douglas Sea State 3.

All details/figures about and without guarantee.

HOLDS & HATCHES

Hatchcover type	MacGregor, hydraulic folding type
Tanktop strength	H1 18.8 mts/sqm, H2+H4 18.7 mts/sqm, H3 27.9 mts/sqm, H5 19.9 mts/sqm

		Length	Breadth (fore/aft)	Height	Grain (cbm)	Bale (cbm)
Hatchcovers	No.1	17.60 m	18.92 m			
	No.2	21.12 m	18.92 m			
	No.3	21.12 m	18.92 m			
	No.4	21.12 m	18.92 m			
	No.5	21.12 m	18.92 m			
Cargo holds	No.1	28.80 m	7.88 m / 23.40 m	18.00 m	12,722.10	12,138.20
	No.2	28.80 m	23.40 m	18.00 m	14,717.40	14,095.90
	No.3	28.80 m	23.40 m	18.00 m	14,659.40	14,056.30
	No.4	28.80 m	23.40 m	18.00 m	14,717.40	14,095.90
	No.5	30.00 m	23.40 m / 9.4 m	18.00 m	14,039.00	13,730.50
Total Capacity					70,855.30	68,116.80

GEAR & ENGINE

Crane type	electro-hydraulic crane
SWL	4 x 30 mt each, max. 24 mt in grab modus with 26 m radius
Outreach	10.00 m beyond ship's rail
Grabs type	SMAG Peiner, hook-on type, radio (remote) controlled
Capacity	4 x 12.5 cbm each

OTHER FITTINGS

Logs fitted	No
Cement holes	Yes, 2 x 700 mm per hold
Ventilation	Natural
Grain fitted	Yes
CO2 fitted	NO
A60 bulkhead	NO
Australian hold ladder	Yes
Strengthened for heavy cargo	Yes