



GENERAL

Name	Christina Selmer
Type	Handysize Samjin 33,660
Built	Sep 11
Flag	Marshall Island
Class	DNV GL
DWAT	33,660 mt on 9.816 m (summer)
TPC	48.29 mts/cm (summer)
Tonnage	23,432 (GT) / 10,758 (NT)
LOA	180.00 m
Beam	30.00 m
Depth	14.70 m

SPEED & CONSUMPTION

Speed	Consumption		
	laden	ballast	
abt. 13.5 kn		abt. 24.0 mt HFO	plus abt. 0.10 mt MDO/day
abt. 12.7 kn		abt. 22.0 mt HFO	plus abt. 0.10 mt MDO/day
abt. 12.5 kn	abt. 24.0 mt HFO		plus abt. 0.10 mt MDO/day
abt. 12.0 kn	abt. 20.5 mt HFO		plus abt. 0.10 mt MDO/day
	idle	working	
Port	abt. 2.8 mt HFO	abt. 4.3 mt HFO	

Figures given basis clean and smooth bottom, deep water, even keel, no negative influence by currents, including 15% sea margin up to and incl. Beaufort Scale Force 4 and Douglas Sea State 3.

All details/figures about and without guarantee.

HOLDS & HATCHES

Hatchcover type		Folding type				
Tanktop strength		Hold 1/2/3/5/7/8/9 – 20 mt/sqm, Hold 4/6 – 22 mt/sqm				
		Length	Breadth (fore/aft)	Height	Grain (cbm)	Bale (cbm)
Hatchcovers	No.1	16.00 m	13.70 m/18.40 m			
	No.2	19.20 m	20.20 m			
	No.3	19.20 m	20.20 m			
	No.4	19.20 m	20.20 m			
	No.5	19.20 m	20.20 m			
Cargo holds	No.1	24.69 m	19.80 m / 8.40 m	15.15 m	7,742.80	7,559.60
	No.2	24.80 m	22.00 m	15.15 m	9,764.70	9,635.50
	No.3	24.80 m	22.00 m	15.15 m	9,809.60	9,666.40
	No.4	24.80 m	22.00 m	15.15 m	9,821.30	9,676.50
	No.5	25.50 m	22.00 m / 12.80 m	15.15 m	9,146.40	9,031.50
Total Capacity					46,284.80	45,569.50

GEAR & ENGINE

Crane type	MacGregor GLB3526-2
SWL	4 x 35 mt each, hook operation
Outreach	11.00 m beyond ship's rail
Grabs type	SMAG Peiner Dual scoop motorgrabs, MZGL 10000-6-B
Capacity	4 x 10 cbm each

OTHER FITTINGS

Logs fitted	presently not fully fitted
Cement holes	Yes, 2 x 700 mm
Ventilation	Yes, electric
Grain fitted	Yes
CO2 fitted	Yes
A60 bulkhead	Yes
Australian hold ladder	Yes
Strengthened for heavy cargo	Yes