



GENERAL

Name	Imke Selmer
Type	Handysize Jiangsu 32,648 dwt
Built	May 2010
Flag	Marshall Islands
Class	ABS
DWAT	32,648 mt on 10.167 m (summer)
TPC	46.00 mts/cm (summer)
Tonnage	20,846 (GT) / 11,800 (NT)
LOA	179.9 m
Beam	28.40 m
Depth	14.10 m

SPEED & CONSUMPTION

Speed	Consumption		
	laden	ballast	
abt. 14.0 kn		abt. 24.5 mt HFO	plus abt. 0.10 mt MDO/Day
abt. 13.5 kn	abt. 24.5 mt HFO		plus abt. 0.10 mt MDO/Day
abt. 12.9 kn		abt. 17.6 mt HFO	plus abt. 0.10 mt MDO/Day
abt. 11.4 kn	abt. 19.8 mt HFO		plus abt. 0.10 mt MDO/Day
	idle	working	
Port	abt. 3.2 mt HFO	abt. 4.0 mt HFO	

Figures given basis clean and smooth bottom, deep water, even keel, no negative influence by currents, including 15% sea margin up to and incl. Beaufort Scale Force 4 and Douglas Sea State 3.

All details/figures about and without guarantee.

HOLDS & HATCHES

Hatchcover type	MacGregor, cylinder folding type
Tanktop strength	20 mt/sqm uniform design load

		Length	Breadth (fore/aft)	Height	Grain (cbm)	Bale (cbm)
Hatchcovers	No.1	14.72 m	17.60 m			
	No.2	20.20 m	19.20 m			
	No.3	20.20 m	19.20 m			
	No.4	20.20 m	19.20 m			
	No.5	18.72 m	19.20 m			
Cargo holds	No.1	14.72 m	17.60 m	15.15 m	7,069.00	6,644.86
	No.2	20.20 m	19.20 m	15.15 m	9,652.10	9,266.02
	No.3	20.20 m	19.20 m	15.15 m	9,052.60	8,690.50
	No.4	20.20 m	19.20 m	15.15 m	9,650.40	9,264.38
	No.5	18.72 m	19.20 m	15.15 m	8,059.50	7,575.93
Total Capacity					43,483.60	41,441.69

GEAR & ENGINE

Crane type	IHI-Wuhan Marine Machinery H305190-240
SWL	4 x 30.5 mt each, hook operation
Outreach	9.80 m beyond ship's rail
Grabs type	SMAG Peiner Motor Dual-scoop grabs, MZGL 100006-B, SWL 15.5 mts
Capacity	4 x 10 cbm each

OTHER FITTINGS

Logs fitted	presently not fully fitted
Cement holes	Yes, 2 x 700 mm
Ventilation	Yes, mechanical
Grain fitted	Yes
CO2 fitted	Yes
A60 bulkhead	Yes
Australian hold ladder	Yes
Strengthened for heavy cargo	Yes