



GENERAL

Name	Levante
Type	Handysize 35k OHBS
Built	December 2004
Flag	Malta
Class	NKK
DWAT	35,061 mts on 11.30 m (summer)
TPC	47.43 mt/cm (summer)
Tonnage	24,960 (GT) / 12,463 (NT)
LOA	188.64 m
Beam	27.68 m
Depth	15.50 m

SPEED & CONSUMPTION

Speed	Consumption	
	laden	ballast
abt. 14.5 kn		abt. 30.0 mt HFO
abt. 14.0 kn	abt. 31.0 mt HFO	
Port	idle	working
	abt. 3.5 mt HFO	abt. 5.0 mt HFO

Figures given basis clean and smooth bottom, deep water, even keel, no negative influence by currents, including 15% sea margin up to and incl. Beaufort Scale Force 4 and Douglas Sea State 3.

All details/figures about and without guarantee.

HOLDS & HATCHES

Hatchcover type	Folding type				
Tanktop strength	Hold 1/2/3/5/7/8/9 – 20 mt/sqm, Hold 4/6 – 22 mt/sqm				
		Length	Breadth (fore/aft)	Height	Grain (cbm)
Hatchcovers	No.1	12.80 m	20.00 m		
	No.2	12.80 m	23.00 m		
	No.3	12.80 m	23.00 m		
	No.4	12.80 m	23.00 m		
	No.5	12.80 m	23.00 m		
	No.6	12.80 m	23.00 m		
	No.7	12.80 m	23.00 m		
	No.8	12.80 m	23.00 m		
	No.9	12.80 m	23.00 m		
Cargo holds	No.1	13.60 m	20.00 m	16.00 m	4,000.00
	No.2	13.60 m	23.00 m	16.00 m	5,012.00
	No.3	16.00 m	23.00 m	16.00 m	5,661.00
	No.4	13.60 m	23.00 m	16.00 m	5,013.00
	No.5	16.00 m	23.00 m	16.00 m	5,640.00
	No.6	13.60 m	23.00 m	16.00 m	5,013.00
	No.7	16.00 m	23.00 m	16.00 m	5,650.00
	No.8	13.60 m	23.00 m	16.00 m	4,895.00
	No.9	13.60 m	23.00 m	13.40 m	3,788.00
Total Capacity					44,672.00

GEAR & ENGINE

SWL	40 mt each
Outreach	max. 24 m
Grabs type	N/A
Capacity	N/A

OTHER FITTINGS

Logs fitted	No
Cement holes	Yes
Ventilation	Mechanical
Grain fitted	Yes
CO2 fitted	Yes
A60 bulkhead	No
Australian hold ladder	Yes
Strengthened for heavy cargo	Yes