



GENERAL

Name	Nordic Dalian
Type	Handysize Seahorse
Built	August 2013
Flag	Liberia
Class	Bureau Veritas
DWAT	37,330 mts on 10.65 m (summer)
TPC	51.0 mt/cm (summer)
Tonnage	24,212 (GT) / 12,860 (NT)
LOA	180.00 m
Beam	30.00 m
Depth	14.70 m

SPEED & CONSUMPTION

Speed	Consumption	
	laden	ballast
abt. 14.0 kn	abt. 24.0 mt HFO	abt. 20.5 mt HFO
abt. 13.0 kn	abt. 20.0 mt HFO	abt. 18.0 mt HFO
abt. 12.0 kn	abt. 16.5 mt HFO	abt. 14.5 mt HFO

Port	idle	working
	abt. 3.0 mt HFO	abt. 4.0 mt HFO

Figures given basis clean and smooth bottom, deep water, even keel, no negative influence by currents, including 15% sea margin up to and incl. Beaufort Scale Force 4 and Douglas Sea State 3.

All details/figures about and without guarantee.

HOLDS & HATCHES

Hatchcover type		TTS Transfolding hatch covers				
Tanktop strength		25 mt/sqm				
		Length	Breadth (fore/aft)	Height	Grain (cbm)	Bale (cbm)
Hatchcovers	No.1	16.00 m	18.70m / 15.00 m			
	No.2	19.20 m	20.30 m			
	No.3	19.20 m	20.30 m			
	No.4	19.20 m	20.30 m			
	No.5	19.20 m	20.30 m			
Cargo holds	No.1	27.40 m	7.80 m / 26.60 m	15,40 m	7,949.00	7,818.00
	No.2	26.00 m	26.60 m	15,40 m	9,789.50	9,525.00
	No.3	26.00 m	26.60 m	15,40 m	9,783.40	9,525.00
	No.4	26.00 m	26.60 m	15,40 m	9,782.60	9,525.00
	No.5	28.20 m	26.60 m / 6.90 m	15,10 m	9,429.50	9,276.00
Total Capacity					46,734.00	45,670.00

GEAR & ENGINE

Crane type	Electro hydraulic Cranes
SWL	4 x 30mt
Outreach	min. 4 m / max. 26 m
Grabs type	No
Capacity	N/A

OTHER FITTINGS

Logs fitted	No
Cement holes	5 x 600 mm diameter per hold
Ventilation	Natural
Grain fitted	Yes
CO2 fitted	Yes
A60 bulkhead	Yes
Australian hold ladder	Yes
Strengthened for heavy cargo	Yes