



GENERAL

| | |
|----------------|---|
| Name | Nordic Incheon |
| Type | Single Deck Bulk Carrier/Handysize Samjin SSI 36k |
| Built | 2018 |
| Flag | Liberia |
| Class | DNV GL |
| DWAT | abt. 35,550 mts on 10.20 m (summer) |
| TPC | abt. 48.50 mt/cm (summer) |
| Tonnage | 22,860 (GT) / 12,082 (NT) |
| LOA | 180.00 m |
| Beam | 30.00 m |
| Depth | 14.70 m |

SPEED & CONSUMPTION

| Speed | Consumption | | |
|--------------|------------------|------------------|----------------------|
| | laden | ballast | |
| abt. 14.0 kn | | abt. 21.0 mt HFO | plus abt. 0.1 mt MGO |
| abt. 13.5 kn | abt. 21.0 mt HFO | | plus abt. 0.1 mt MGO |
| abt. 12.5 kn | | abt. 15.5 mt HFO | plus abt. 0.1 mt MGO |
| abt. 12.0 kn | abt. 15.5 mt HFO | | plus abt. 0.1 mt MGO |
| | idle | working | |
| | abt. 2.80 mt HFO | abt. 4.3 mt HFO | plus abt. 0.1 mt MGO |

Figures given basis clean and smooth bottom, deep water, even keel, no negative influence by currents, including 15% sea margin up to and incl. Beaufort Scale Force 4 and Douglas Sea State 3.
All details/figures about and without guarantee.

HOLDS & HATCHES

| Hatchcover type | TTS, Electro hydraulic end-folding type | | | | | |
|------------------|---|---------|--------------------|---------|-------------|------------|
| Tanktop strength | 22 mt/sqm | | | | | |
| | | Length | Breadth (fore/aft) | Height | Grain (cbm) | Bale (cbm) |
| Hatchcovers | No.1 | 16.80 m | 15.00 m | | | |
| | No.2 | 19.20 m | 19.20 m | | | |
| | No.3 | 19.20 m | 19.20 m | | | |
| | No.4 | 19.20 m | 19.20 m | | | |
| | No.5 | 19.20 m | 19.20 m | | | |
| Cargo holds | No.1 | 26.40 m | 21.70 m | 13.50 m | 8,382,.80 | 8,047.496 |
| | No.2 | 24.00 m | 23.25 m | 13.50 m | 9,919.22 | 9,522.453 |
| | No.3 | 24.00 m | 23.25 m | 13.50 m | 9,932.56 | 9,535.266 |
| | No.4 | 24.00 m | 23.25 m | 13.50 m | 9,932.57 | 9,535.270 |
| | No.5 | 26.40 m | 23.25 m | 13.50 m | 9,417.93 | 9,041.217 |
| Total Capacity | | | | | 47,585.10 | 45,681.702 |

GEAR & ENGINE

| | |
|------------|------------------------------------|
| Crane type | Electro hydraulic single jib crane |
| SWL | 4 x 35 mt each |
| Outreach | max. 26 m |
| Grabs type | No |
| Capacity | N/A |

OTHER FITTINGS

| | |
|------------------------------|---|
| Logs fitted | No |
| Cement holes | Yes 5 x 760 mm / 600 mm diameter per hold |
| Ventilation | mechanical |
| Grain fitted | Yes |
| CO2 fitted | Yes |
| A60 bulkhead | Yes |
| Australian hold ladder | Yes |
| Strengthened for heavy cargo | Yes |