



GENERAL

Name	Nordic Malmoe
Type	Handysize Seahorse
Built	March 2011
Flag	Liberia
Class	American Bureau of Shipping
DWAT	35,843 mts on 10.343 m (summer)
TPC	50.90 mt/cm (summer)
Tonnage	24,212 (GT) / 12,108 (NT)
LOA	180.00 m
Beam	30.00 m
Depth	14.76 m

SPEED & CONSUMPTION

Speed	Consumption		
	laden	ballast	
abt. 14.0 kn	abt. 24.5 mt HFO	abt. 20.5 mt HFO	
abt. 13.0 kn	abt. 20.5 mt HFO	abt. 18.0 mt HFO	
abt. 12.0 kn	abt. 16.5 mt HFO	abt. 14.5 mt HFO	
Port	idle abt. 3.5 mt HFO	working abt. 5.5 mt HFO	plus abt. 0.1 mt MDO

Figures given basis clean and smooth bottom, deep water, even keel, no negative influence by currents, including 15% sea margin up to and incl. Beaufort Scale Force 4 and Douglas Sea State 3.

All details/figures about and without guarantee.

HOLDS & HATCHES

Hatchcover type		TTS, Electro hydraulic end-folding type				
Tanktop strength		22.0 mt/sqm				
		Length	Breadth (fore/aft)	Height	Grain	Bale
Hatchcovers	No.1	16.00 m	18.70 m / 15.00 m			
	No.2	19.20 m	20.30 m			
	No.3	19.20 m	20.30 m			
	No.4	19.20 m	20.30 m			
	No.5	19.20 m	20.30 m			
Cargo holds	No.1	27.50 m	26,00 m	15,10 m	7,961.90	7,832.00
	No.2	26.30 m	26,60 m	15,50 m	9,790.40	9,525.00
	No.3	26.20 m	26,60 m	15,50 m	9,790.90	9,525.00
	No.4	26.20 m	26,60 m	15,50 m	9790.70	9,525.00
	No.5	28.30 m	26,60 m	15,10 m	9,428.20	9,276.00
Total Capacity					46,762.10	45,683.00

GEAR & ENGINE

Crane type	Electro hydraulic cranes – not combinable
SWL	4 x 30 mt each
Outreach	min. 3,60 m / max. 25,00m
Grabs type	No
Capacity	N/A

OTHER FITTINGS

Logs fitted	No
Cement holes	Yes
Ventilation	Natural
Grain fitted	Yes
CO2 fitted	Yes
A60 bulkhead	Yes
Australian hold ladder	Yes
Strengthened for heavy cargo	Yes