



GENERAL

Name	Nordic Nanjing
Type	Handysize Seahorse
Built	April 2013
Flag	Liberia
Class	American Bureau of Shipping
DWAT	34,620 mts on 10.10 m (summer)
TPC	50.8 mt/cm (summer)
Tonnage	24,187 (GT) / 11,602 (NT)
LOA	180.00 m
Beam	30.00 m
Depth	14.70 m

SPEED & CONSUMPTION

Speed	laden	ballast
abt. 14.0 kn	abt. 24.0 mt HFO	abt. 20.5 mt HFO
abt. 13.0 kn	abt. 20.0 mt HFO	abt. 18.0 mt HFO
abt. 12.0 kn	abt. 16.5 mt HFO	abt. 14.5 mt HFO
Port	idle	working
	abt. 3.0 mt HFO	abt. 4.0 mt HFO

Figures given basis clean and smooth bottom, deep water, even keel, no negative influence by currents, including 15% sea margin up to and incl. Beaufort Scale Force 4 and Douglas Sea State 3.

All details/figures about and without guarantee.

HOLDS & HATCHES

Hatchcover type	TTS Transfolding hydraulic hatch covers					
Tanktop strength	25.0 mt/sqm					
		Length	Breadth (fore/aft)	Height	Grain	Bale
Hatchcovers	No.1	16.00 m	18.70 m / 15.00 m			
	No.2	19.20 m	20.30 m			
	No.3	19.20 m	20.30 m			
	No.4	19.20 m	20.30 m			
	No.5	19.20 m	20.30 m			
Cargo holds	No.1	27.50 m	7.85 m / 26.00 m	15.10 m	7,949.00	7,819.00
	No.2	26.20 m	26.60 m	15.50 m	9,789.50	9,525.00
	No.3	26.20 m	26.60 m	15.50 m	9,783.40	9,517.00
	No.4	26,20 m	26.60 m	15.50 m	9,782.60	9,517.00
	No.5	28.30 m	26.60 m / 6.50 m	15.10 m	9,429.50	9,276.00
Total Capacity					46,733.00	45,654.00

GEAR & ENGINE

Crane type	Electro hydraulic cranes
SWL	4 x 30 mt each
Outreach	max. 26.2 m
Grabs type	No
Capacity	N/A

OTHER FITTINGS

Logs fitted	No
Cement holes	No
Ventilation	Natural
Grain fitted	Yes (5 x 600 mm each hatch)
CO2 fitted	Yes
A60 bulkhead	Yes
Australian hold ladder	Yes
Strengthened for heavy cargo	Yes