



GENERAL

Name	Nordic Skagen
Type	Handysize
Built	October 2010
Flag	Liberia
Class	DNV-GL
DWAT	34,900 mts on 9.99 m (summer)
TPC	48.81 mt/cm (summer)
Tonnage	23,548 (GT) / 10,838 (NT)
LOA	185.14 m
Beam	30.00 m
Depth	14.75 m

SPEED & CONSUMPTION

Speed	laden	ballast	
abt. 13.5 kn	abt. 25.0 mts HFO	abt. 23.0 mts HFO	plus abt. 1.8 mt HFO/AUX
abt. 13.0 kn	abt. 24.3 mts HFO	abt. 21.8 mts HFO	plus abt. 1.8 mt HFO/AUX
abt. 12.0 kn	abt. 22.8 mts HFO	abt. 21.0 mts HFO	plus abt. 1.8 mt HFO/AUX
Port	idle	working	
	abt. 1.8 mts HFO	abt. 3.3 mts HFO	plus abt. 1.5 mt HFO/AUX

Figures given basis clean and smooth bottom, deep water, even keel, no negative influence by currents, including 15% sea margin up to and incl. Beaufort Scale Force 4 and Douglas Sea State 3.

All details/figures about and without guarantee.

HOLDS & HATCHES

Hatchcover type	End-folding, hydraulic operated				
Tanktop strength	22 mt/sqm				
		Length	Breadth (fore/aft)	Height	Grain
Hatchcovers	No.1	18.40 m	15.00 m		
	No.2	20.00 m	23.00 m		
	No.3	20.00 m	23.00 m		
	No.4	20.00 m	23.00 m		
	No.5	20.00 m	23.00 m		
Cargo holds	No.1	29.40 m	3.20 m / 23.40 m	14.90 m	7,169.00
	No.2	27.00 m	23.62 m / 27.00 m	15.17 m	9,476.10
	No.3	27.00 m	27.00 m	14.90 m	9,671.80
	No.4	27.00 m	26.60 m	14.90 m	9,673.20
	No.5	28.00 m	11.20 m / 23.40 m	14.90 m	9,045.10
Total Capacity					45,035.30

GEAR & ENGINE

Crane type	TTS Deck Cranes
SWL	4 x 30 mt each
Outreach	min. 3.6 m / max. 25.0 m
Grabs type	No
Capacity	N/A

OTHER FITTINGS

Logs fitted	No
Cement holes	1 x 800 mm + 4 x 500 mm diameter per hold
Ventilation	Electrical
Grain fitted	Yes
CO2 fitted	Yes
A60 bulkhead	Yes
Australian hold ladder	yes
Strengthened for heavy cargo	Yes, cargo holds 2+4 may be empty