



GENERAL

Name	Nordic Yarra
Type	Handysize Seahorse
Built	June 2014
Flag	Liberia
Class	Bureau Veritas
DWAT	37,205 mt on 10.65 m (summer)
TPC	51.0 mt/cm (summer)
Tonnage	24,212 (GT) / 12,860 (NT)
LOA	180.00 m
Beam	30.00 m
Depth	14.70 m

SPEED & CONSUMPTION

Speed	Consumption	
	laden	ballast
abt. 14.0 kn	abt. 25.0 mt HFO	abt. 21.5 mt HFO
abt. 13.0 kn	abt. 21.0 mt HFO	abt. 19.0 mt HFO
abt. 12.0 kn	abt. 17.5 mt HFO	abt. 15.5 mt HFO
Port	idle	working
	abt. 3.0 mt HFO	abt. 4.0 mt HFO

Figures given basis clean and smooth bottom, deep water, even keel, no negative influence by currents, including 15% sea margin up to and incl. Beaufort Scale Force 4 and Douglas Sea State 3.

All details/figures about and without guarantee.

HOLDS & HATCHES

Hatchcover type		TTS Transfolding, Electro-hydraulic type				
Tanktop strength		25 mt/sqm				
		Length	Breadth (fore/aft)	Height	Grain	Bale
Hatchcovers	No.1	16.00 m	18.70 m / 15.00 m			
	No.2	19.20 m	20.30 m			
	No.3	19.20 m	20.30 m			
	No.4	19.20 m	20.30 m			
	No.5	19.20 m	20.30 m			
Cargo holds	No.1	27.40 m	26.60 m / 7.60 m	15.40 m	7,948.00	7,818.00
	No.2	26.00 m	26.60 m	15.40 m	9,790.00	9,525.00
	No.3	26.00 m	26.60 m	15.40 m	9,782.00	9,525.00
	No.4	26.00 m	26.60 m	15.40 m	9,782.00	9,525.00
	No.5	28.20 m	26.60 m	15.10 m	9,428.00	9,276.00
Total Capacity					46,733.00	45,670.00

GEAR & ENGINE

Crane type	MacGregor, Electro-hydraulic deck cranes
SWL	4 x 30,0 mt each
Outreach	12,20 m beyond ship's rail
Grabs type	No
Capacity	N/A

OTHER FITTINGS

Logs fitted	No
Cement holes	5 x 690 mm / 420 mm diameter per hold
Ventilation	Natural
Grain fitted	Yes
CO2 fitted	Yes
A60 bulkhead	Yes
Australian hold ladder	Yes
Strengthened for heavy cargo	Yes