



GENERAL

Name	Alentejo
Type	Seahorse 35k
Built	February 2013
Flag	Singapore
Class	ABS
DWAT	36,041 mts on 10.315 m (summer)
TPC	50.80 mt/cm (summer)
Tonnage	24,166 (GT) / 12,061 (NT)
LOA	180.00 m
Beam	30.00 m
Depth	14.71 m

SPEED & CONSUMPTION

Speed	Consumption	
	laden	ballast
abt. 14.0 kn abt. 13.5 kn	abt. 24.0 mt HFO	abt. 22.5 mt HFO
Port	idle	working
	abt. 3.7 mt HFO	abt. 5.5 mt HFO

Figures given basis clean and smooth bottom, deep water, even keel, no negative influence by currents, including 15% sea margin up to and incl. Beaufort Scale Force 4 and Douglas Sea State 3.

All details/figures about and without guarantee.

HOLDS & HATCHES

Hatchcover type	Folding type		Height	Grain (cbm)	
Tanktop strength	22 mt/sqm				
Hatchcovers	No.1	Length	Breadth (fore/aft)		
	No.2	16.00 m	18.70 m / 15.00 m		
	No.3	19.20 m	20.30 m		
	No.4	19.20 m	20.30 m		
	No.5	19.20 m	20.30 m		
Cargo holds	No.1	Length	Breadth (fore/aft)	Height	Grain (cbm)
	No.2	27.50 m	15.69 / 26.00 m	13.70 m	7,948.00
	No.3	26.20 m	26.60 m	13.70 m	9,790.00
	No.4	26.20 m	26.60 m	13.70 m	9,791.00
	No.5	26.20 m	26.60 m	13.70 m	9,791.00
	No.5	28.30 m	26.60 m	13.70 m	9,428.00
Total Capacity					46,748.00

GEAR & ENGINE

SWL	30 mt each / 24 mt each when using grabs
Outreach	max. 26m
Grabs type	N/A
Capacity	each 12 cbm

OTHER FITTINGS

Logs fitted	No
Cement holes	Yes
Ventilation	Mechanical
Grain fitted	Yes
CO2 fitted	Yes
A60 bulkhead	Yes
Australian hold ladder	Yes
Strengthened for heavy cargo	Yes