



GENERAL

| | |
|----------------|--------------------------------|
| Name | Star Dalmatia |
| Type | Supramax 51k OHBS |
| Built | January 2011 |
| Flag | Marshall Islands |
| Class | ABS |
| DWAT | 51.593 mts on 12,40 m (summer) |
| TPC | 59,42 mt/cm (summer) |
| Tonnage | 33.601 (GT) / 16.737 (NT) |
| LOA | 199,90 m |
| Beam | 32,26 m |
| Depth | 16,99 m |

SPEED & CONSUMPTION

| Speed | Consumption | |
|------------------------------|------------------|------------------|
| | laden | ballast |
| abt. 14,5 kn abt. 14,0 kn | abt. 31.0 mt HFO | abt. 29.0 mt HFO |
| Port | idle | working |
| | abt. 2.0 mt HFO | abt. 5.0 mt HFO |

Figures given basis clean and smooth bottom, deep water, even keel, no negative influence by currents, including 15% sea margin up to and incl. Beaufort Scale Force 4 and Douglas Sea State 3.
All details/figures about and without guarantee.

HOLDS & HATCHES

| Hatchcover type | | Folding type | | | |
|-----------------------|------|--------------|--------------------|---------|-------------------|
| Tanktop strength | | 22 mt/sqm | | | |
| | | Length | Breadth (fore/aft) | Height | Grain (cbm) |
| Hatchcovers | No.1 | 13.50 m | 16.72 m | | |
| | No.2 | 13.50 m | 23.28 m | | |
| | No.3 | 16.70 m | 28.20 m | | |
| | No.4 | 16.70 m | 28.20 m | | |
| | No.5 | 16.70 m | 28.20 m | | |
| | No.6 | 16.70 m | 28.20 m | | |
| | No.7 | 16.70 m | 28.20 m | | |
| | No.8 | 15.90 m | 28.20 m | | |
| | No.9 | 13.50 m | 28.20 m | | |
| Cargo holds | No.1 | 12.80 m | 16.02 m | 21.30 m | 3,276.400 |
| | No.2 | 12.80 m | 22.58 m | 21.30 m | 5,741.300 |
| | No.3 | 16.00 m | 27.50 m | 17.30 m | 7,612.000 |
| | No.4 | 16.00 m | 27.50 m | 17.30 m | 7,612.000 |
| | No.5 | 16.00 m | 27.50 m | 17.30 m | 7,612.000 |
| | No.6 | 16.00 m | 27.50 m | 17.30 m | 7,612.000 |
| | No.7 | 16.00 m | 27.50 m | 17.30 m | 7,612.000 |
| | No.8 | 15.20 m | 27.50 m | 17.30 m | 7,036.000 |
| | No.9 | 12.80 m | 27.50 m | 14.60 m | 4,300.700 |
| Total Capacity | | | | | 58,415.100 |

GEAR & ENGINE

| | |
|-------------------|------------|
| SWL | 40 mt each |
| Outreach | max. 32 m |
| Grabs type | N/A |
| Capacity | N/A |

OTHER FITTINGS

| | |
|-------------------------------------|------------|
| Logs fitted | No |
| Cement holes | Yes |
| Ventilation | Mechanical |
| Grain fitted | Yes |
| CO2 fitted | Yes |
| A60 bulkhead | No |
| Australian hold ladder | Yes |
| Strengthened for heavy cargo | Yes |