



GENERAL

Name	Nordic BC Munich
Type	Handysize Bulk Carrier
Built	July 2012
Flag	Liberia
Class	ABS
DWAT	34,827.00 on 10.10m (Summer)
TPC	50.80 mt/cm (laden)
Tonnage	24,187 (GT) / 11,565 (NT)
LOA	180.00 m
Beam	30.00 m
Depth	14.70 m

SPEED & CONSUMPTION

Speed	Consumption		
	laden	ballast	
abt. 14.0 kn	abt. 27.5 mt HFO	abt. 22.9 mt HFO	plus abt. 0.1 mt MDO
abt. 13.0 kn	abt. 22.0 mt HFO	abt. 19.0 mt HFO	plus abt. 0.1 mt MDO
abt. 12.0 kn	abt. 19.1 mt HFO	abt. 16.8 mt HFO	plus abt. 0.1 mt MDO
Port	idle	working	
	abt. 1.5 mt HFO	abt. 4.5 mt HFO	plus abt. 0.1 mt MDO

Figures given basis clean and smooth bottom, deep water, even keel, no negative influence by currents, including 15% sea margin up to and incl. Beaufort Scale Force 4 and Douglas Sea State 3.

All details/figures about and without guarantee.

HOLDS & HATCHES

Hatchcover type		5Weather Tight, End Folding Type				
Tanktop strength		22mt/sqm				
		Length	Breadth (fore/aft)	Height	Grain (cbm)	Bale (cbm)
Hatchcovers	No.1	16.00 m	18.70 m / 15.0 m			
	No.2	19.20 m	20.30 m			
	No.3	19.20 m	20.30 m			
	No.4	19.20 m	20.30 m			
	No.5	19.20 m	20.30 m			
Cargo holds	No.1	27.45 m	7.56m/18.29m/26.41m	15.10 m	7,962.00	7,832.00
	No.2	26.15 m	26.54 m	15.40 m	9,790.00	9,525.00
	No.3	26.15 m	26.54 m	15.40 m	9,791.00	9,525.01
	No.4	26.15 m	26.54 m	15.40 m	9,791.01	9,525.02
	No.5	28.24 m	25.87m/13.24m/6.44m	15.10 m	9,428.00	9,276.00
Total Capacity					46,762.00	45,683.00

GEAR & ENGINE

Crane type	MacGregor Electro Hydraulic
SWL	4 x 30.0 mt each
Outreach	26,20 m
Grabs type	No
Capacity	4 x 12 CBM / Peiner remote control type

OTHER FITTINGS

Logs fitted	No
Cement holes	5, 60, Centre and each corner
Ventilation	Natural
Grain fitted	Yes
CO2 fitted	Yes
A60 bulkhead	Yes
Australian hold ladder	Yes
Strengthened for heavy cargo	Yes